



## Mobil SHC™ PM Series

Mobil Industrial, United States

Paper Machine Lubricants

### Product Description

Mobil SHC™ PM Series products are superior performance synthetic lubricants specifically designed for the most demanding industrial paper machine circulating systems. The Mobil SHC PM Series oils are formulated to provide outstanding protection of gears and bearings operating under the most severe conditions. They have very low pour points and a naturally high viscosity index (VI) which helps ensure good low temperature start-up while maintaining excellent viscosity characteristics at very high temperatures. The fluids are very shear stable and maintain viscosity control even when subjected to severe mechanical shear in heavily loaded bearings and gears. Their low traction coefficient and high viscosity index can help result in lower energy consumption and reduced component operating temperatures.

To develop the latest Mobil SHC technology for Mobil SHC PM Series oils, ExxonMobil product formulation scientists chose select base oils because of their exceptional thermal/oxidative resistance potential and combined them with a balanced additive system, which complement the inherent benefits of the base oils to attain high performance standards. These fluids permit the use of higher steam pressures, temperatures and machine speeds common in high output paper machines and calendar rolls. Their outstanding hydrolytic stability and filterability assure excellent performance in the presence of water and the ability to retain effective filtration even at very fine filtration levels. They readily separate water and retain their colour characteristics for extended periods of operation under severe conditions.

### Features and Benefits

The Mobil SHC PM Series oils represent a technological advance in paper machine lubrication. Their excellent performance capabilities in the areas of wear protection, enhanced oxidation stability, chemical stability, effective rust and corrosion protection, colour stability, and filterability not only prolong maintenance service intervals but can improve machine performance and increase production capacity. This can result in less required maintenance and longer equipment life.

Features	Advantages and Potential Benefits
Excellent Wide Temperature Performance	Easier start-up and improved lubrication at cold starts Extra margin of protection at elevated temperatures Better control of feed rates
Exceptional Wear Protection	Improved bearing and gear performance
Outstanding Oxidation and Thermal Stability	Longer oil life Lower filter replacement costs Cleaner systems Reduction of system deposits
Effective Water Separation Properties	Allows easier removal of water Reduces formation of undesirable emulsions in systems
Low Traction Coefficient	Reduced energy consumption Lower operating temperatures Reduced wear
Excellent Filterability	Keeps oil lines and flow control mechanisms free of deposits Improved oil flow and cooling performance Lowers filter replacement costs
High Level Rust and Corrosion Protection	Protects gears and bearings in wet environments Provides vapour space protection for areas of bearing and gear cavities above normally wetted surfaces

### Applications

- Lubrication of severe industrial paper machine circulating systems

- Application involving circulation systems operating over a wide temperature range such as calendar rolls
- Systems that must be started and brought on line quickly
- Circulation systems lubricating gears and bearings

## Typical Properties

Mobil SHC PM Series	150	220	320	460
ISO Viscosity Grade	150	220	320	460
Viscosity, ASTM D 445				
cSt @ 40° C	158	225	325	465
cSt @ 100° C	18.9	25.6	34.7	44.8
Viscosity Index, ASTM D 2270, typical	124	127	130	137
FZG 4-Square Load Support, DIN 51354, fail stage	11	11	11	11
Rust Characteristics, Proc A and B, ASTM D 665	Pass	Pass	Pass	Pass
Hydrolytic Stability (Acid Number Change),ASTM D 2619, mgKOH/g	0	0	0	0
Copper Strip Corrosion, 24h @ 100° C, ASTM D 130, rating	1B	1B	1B	1B
Demulsibility, minutes to 40/40/0, 82° C	15	25	30	30
Pour Point, °C, ASTM D 97, max	-39	-36	-33	-27
Flash Point, °C, ASTM D 92, min	220	220	220	220
Specific Gravity 15° C/15° C, ASTM D 1298	0.857	0.863	0.865	0.874

## Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

09-2017


Exxon Mobil Corporation  
22777 Springwoods Village Parkway  
Spring TX 77389

1-800-ASK MOBIL (275-6624)

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

**ExxonMobil**



© Copyright 2003-2017 Exxon Mobil Corporation. All Rights Reserved.